


8 Goshawk Road  
New Germany  
Po Box 378  
New Germany  
3620  
Tel: 031 705 4666/Fax: 031 705 3947  
Email: prodecpaints@mweb.co.za



Name: QUICK DRY ENAMEL WHITE Date Issued : 2009/11/16



### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Name : Q.D ENAMEL WHITE Code : 04300 Date Issued : 2009/11/16  
CAS no. : Not applicable EC no. : Not applicable EcoChem : 99.AM.01  
UN No. : 1263 EAC : 127 Hazchem : 3[Y]E Kemler : 30 SAPMA : 2-H-E  
In emergency contact PRODEC PAINTS (MARK SMIT) at 031 7054666

### SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

EC Classification : F Xn R11,20/21,65,38 S36/37,02,13,16,43A,51,62

#### HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

XYLENE <51 %  
[CAS #: 001330-20-7] [E.C. #: 601-022-00-9]  
EEC Labels : Xn OEL 435mg OEL 100ppm STOEL 650.mg STOEL 150.ppm RL+ S

TOLUENE <8 %  
[CAS #: 000108-88-3] [E.C. #: 601-021-00-3]  
EEC Labels : F Xn OEL 188mg OEL 50ppm STOEL 560mg STOEL 150ppm RL+ S

WHITE SPIRIT (WS3) Xn <0 %  
[CAS #: 064742-88-7] [E.C. #: 649-405-00-X]  
EEC Labels : Xn OEL 575mg OEL 100ppm STOEL 720mg STOEL 125ppm RL

UPDATE FEB 08  
[CAS #: ] [E.C. #: ]  
EEC Labels :

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

### SECTION 3. HAZARDS IDENTIFICATION

SAPMA Health Rating : 2-MODERATE - Temporary or minor injury possible even if treatment given  
Inhalation : Irritating, narcotic. Can affect CNS.  
Skin : Irritating, risk of dermatitis. May be absorbed.  
Eyes : Irritating.  
Ingestion : Irritating and nauseating.  
May have short term environmental effects. Contain, monitor & remove.

### SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. In case of discomfort seek medical attention.  
Skin : Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention  
Eyes : Rinse immediately with plenty of water. Seek medical advice.  
Ingestion : Wash mouth with plenty of water. Do NOT induce vomiting. seek medical attention.

### SECTION 5. FIRE FIGHTING MEASURES

Highly flammable with toxic fumes.  
Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard!  
Foam. Dry powder. Fog to cool and control. Do NOT use water jets.  
Cool containers in case of fire.

### SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Keep out of drains and sewers

### SECTION 7. HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular.  
No open flames. No smoking. No sparks.  
Keep containers cool. Avoid free fall of liquid - use earthing.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAPMA Rating : 2-H-E PPE : Respirator and Eye protection

Inhalation : In case of insufficient ventilation, use suitable respiratory protection.

Skin : Use barrier cream and impervious gloves.

Eyes : Use face shield or goggles. Avoid direct contact.

Ingestion : Observe the rules of hygiene. Wash before eating, drinking or smoking.

OEL Type : Mixture- Mixture - See Section 2 Skin



## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical class : PAINT PRODUCT Description : Viscous liquid Smell : Pungent SG : to be established pH : to be established Boil. pt (°C) : >35 FlashPoint (°C) : <23

## SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions Could generate static - USE EARTHING No reaction with fire-fighting water

## SECTION 11. TOXICOLOGICAL INFORMATION

LD50 Oral: >500 mg (derived)

## SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove.

## SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

## SECTION 14. TRANSPORT INFORMATION

UN No. : 1263 : PAINT PRODUCT Packing group : II IMO Class : 3.2 EAC : 127 Hazchem : 3[Y]E Kemler : 30



## SECTION 15. REGULATORY INFORMATION

EC no. : Not applicable

EC Classification : F Xn R11,20/21,65,38 S36/37,02,13,16,43A,51,62

R11 - Highly Flammable

R20/21 - Harmful by inhalation and contact with the skin

R65 - Harmful: May cause lung damage if swallowed.

R38 - Irritating to the skin

S36/37 - Wear suitable protective clothing and gloves

S2 - Keep out of reach of children. (Retail sales items)

S13 - Keep away from food, drink and animal feeding stuffs

S16 - Keep away from sources of ignition - No smoking

S43A - In case of fire, use water fog, foam or powder - Do not use water jets!

S51 - Use only in well ventilated areas

S62 - If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label.

" - Not found in file



## SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)

OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)

SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)

All information is given in good faith but without guarantee in respect of accuracy.

No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue : 2009/11/16 Generic last modified : 2008/06/09 Specific last modified : 2008/06/09)