



DÉCOR CHOICE RANGE TECHNICAL DATA SHEET

ACRYLIC ROOF COAT

PRODUCT DESCRIPTION

Prodec Acrylic Roof Coat is a tough, durable waterbased roof paint with a low sheen finish.

PRODUCT FEATURES

- Excellent adhesion
- Excellent application properties

APPLICATION AREAS

- Cement and fibre-cement tiles
- Primed metal substrates

SURFACE PREPARATION

- **Rusted metal:** affected areas need to be cleaned back to bright metal and spot primed with Prodec Waterbased Metal/Galvanised Primer.
- **New metal:** surfaces need to be abrasively degreased to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break-free. After drying, the whole substrate is coated with Prodec Water Based Metal/Galvanised Primer.
- **Uncoated concrete/fibre Cement surfaces:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks and coat with Prodec Bonding liquid
- **Uncoated, weathered or new fibre-cement roofs:** remove all dust, foreign material or fungal and algal growth, and if friable or powdery seal with Prodec Bonding Liquid.
- **Raw Plaster:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks and coat with Prodec Plaster Primer.
- **Previously Painted Surfaces:** remove all loose, flaking or bubbling paint; remove all dust, foreign material or fungal and algal growth. Allow to dry. If then powdery or friable, seal with Prodec Bonding Liquid.

APPLICATION PROCEDURE

- Stir well before use.
- Use a brush, roller or airless-spray to apply a generous coat of Prodec Acrylic Roof Coat.
- Allow 4-6 hours to dry before recoating.
- Use a brush, roller or airless-spray to apply a second generous coat

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- Do not apply to exterior if rain is likely within 4-6 hours of application.
- Prodec Acrylic Roof Coat is ready for use unthinned: thinning will reduce its hiding power.
- For best results use 2 coats of Prodec Acrylic Roof Coat.
- The spreading rate will vary with porosity and type of substrate. For uncoated new work 1 litre will cover about 6-8m². For subsequent coats and when applied to sealed or previously painted substrates, 1 litre will cover 8-10m².
- Clean application equipment with clean tap water.

COLOURS AND QUANTITIES

- Available in 7 Standard Colours
- 5L and 20L

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za