



DÉCOR CHOICE TECHNICAL DATA SHEET

HI-COVER ACRYLIC

PRODUCT DESCRIPTION

Prodec Hi-Cover Acrylic is a waterbased, economic, matt coating for walls and ceilings.

PRODUCT FEATURES

- Excellent, no-mess application properties
- Very good opacity/hiding-power
- Economic

APPLICATION AREAS

- Plaster, hardboard and fibre-cement ceilings or walls

SURFACE PREPARATION

- **Uncoated concrete surfaces:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks.
- **Uncoated weathered or new fibre-cement surfaces:** remove all dust foreign material or fungal and algal growth. If friable or powdery, seal with Prodec Bonding Liquid.
- **Raw Plaster:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks.
- **Previously Painted Surfaces:** remove all loose, flaking or bubbling paint. Remove all dust, foreign material or fungal and algal growth. Allow to dry. If then powdery or friable, seal with Prodec Bonding Liquid.

APPLICATION PROCEDURE

- Always stir well before use.
- Use a brush, roller or airless spray to apply a generous coat of Prodec Hi-Cover Acrylic.
- Allow 2-3 hours to dry before recoating.
- Apply a second generous coat with a brush, roller or airless spray.

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- Do not apply to exterior if rain is likely within 4-6 hours of application.
- Prodec Hi-Cover Acrylic is ready for use unthinned. Thinning will reduce its hiding power.
- For best results use 2 coats of Prodec Hi-Cover Acrylic.
- The spreading rate will vary with porosity and type of substrate. For uncoated new work 1 litre will cover about 6-8m². For subsequent coats and when applied to sealed or previously painted substrates, 1 litre will cover 8-10m².
- Clean application equipment with clean tap water.
- **Never** use Prodec Hi-Cover Acrylic as a replacement for Prodec Plaster Primer or Prodec Bonding Liquid for any paint type. It may result in failure.

COLOUR RANGE & QUANTITIES

- Available in white and standard colours
- 5L and 20L

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za