



PURE ACRYLIC WATERBASED COATINGS TECHNICAL DATA SHEET

RIPPLECOAT

PRODUCT DESCRIPTION

Prodec Ripplecoat is a waterbased, flexible, pure acrylic coating providing a ripple texture. It can be used for long-life exterior protection of buildings, and as a feature on interior walls or ceilings. It is excellent for hiding plaster imperfections and small hairline cracks.

PRODUCT FEATURES

- Highly durable
- Ripple effect to hide surface imperfections
- Water resistant
- Good adhesion
- Excellent flexibility; moves with the substrate; covers small plaster cracks
- Estimated Dry Film Thickness: 40-45 Microns per coat when applied at 4m²/L
- Prodec 8 Year Quality Warranty (Subject to terms and conditions available at www.prodecpaints.co.za)

APPLICATION AREAS

- New or weathered cement tiles or fibre-cement sheeting
- Plaster or previously painted substrates

SURFACE PREPARATION

- **Uncoated cement surfaces:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks and coat with Prodec Plaster Primer.
- **Uncoated weathered or new fibre-cement surfaces:** remove all dust, foreign material or fungal and algal growth and if friable or powdery, seal with Prodec Bonding Liquid.
- **Raw Plaster:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks and coat with Prodec Plaster Primer.
- **Previously Painted Surfaces:** remove all loose, flaking or bubbling paint, as well as all dust, foreign material or fungal and algal growth. Allow to dry. If then powdery or friable, seal with Prodec Bonding liquid.

APPLICATION PROCEDURE

- Stir well before use.
- Use a lambswool roller to apply a generous coat of Prodec Ripplecoat. If a higher texture is required, use a foam textured roller.
- Allow 4-6 hours to dry before recoating with Prodec Ripplecoat in the same manner as the first.

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- Do not apply to exterior if rain is likely within 4-6 hours of application.
- Prodec Ripplecoat is ready for use unthinned, thinning will reduce its hiding power and texture.
- For best results use 2 coats of Prodec Ripplecoat.
- The spreading rate will vary with porosity and type of substrate. For uncoated new work 1 litre will cover about 2-4m². For subsequent coats and when applied to sealed or previously painted substrates, 1 litre will cover 4-5m².
- Clean application equipment with clean tap water.

COLOUR RANGE AND QUANTITIES

- Available in white and pastel shades from tinting system
- 5/20 litres

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za