



SOLVENT-BASED COATINGS TECHNICAL DATA SHEET

STOEP PAINT

PRODUCT DESCRIPTION

Prodec Stoep Paint is a solvent-based semi-gloss floor coating for floor areas that need a washable, alkali and abrasion resistant coating.

PRODUCT FEATURES

- Good washability
- Humidity and abrasion resistant
- Excellent adhesion to a range of properly prepared flooring substrates
- Excellent, no-mess application properties
- Excellent flow and levelling
- High hiding power and film build
- Alkali-resistant when applied to dry cement floors (15% maximum moisture level)

APPLICATION AREAS

- Dry (15% maximum moisture level) cement floors
- Primed metal and wooden substrates

SURFACE PREPARATION

- **Rusted metal:** affected areas need to be cleaned back to bright metal using Prodec Rust Neutraliser and spot primed with Prodec Metal Etch Primer/Prodec Waterbased Metal/Galvanised Primer.
- **New metal:** surfaces need to be abrasively degreased using Prodec Galvanised Iron Cleaner to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break-free. After drying, the whole substrate is coated with Prodec Metal Etch Primer/Prodec Waterbased Metal/Galvanised Primer.
- **New wooden floors:** prime bare wooden areas with 1 coat of Prodec Wood Primer Pink allowing 18-24 hours drying time. Overcoat with 1 coat of Prodec General Purpose Undercoat White allowing 18-24 hours drying time before applying top coats.
- **Dry (maximum moisture 15%) uncoated concrete surfaces:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks with a suitable flexible sealant.
- **Previously Painted Surfaces:** remove all loose, flaking or bubbling paint. Remove all dust, foreign material or fungal and algal growth. Allow to dry. Spot prime with Prodec Stoep Paint thinned 10% with Prodec Mineral Turpentine.

APPLICATION PROCEDURE

- Stir well before use.
- Use a brush or mohair roller to apply a generous coat of Prodec Stoep Paint. (For new concrete surfaces, thin 10% with Prodec Mineral Turpentine to aid penetration)
- Allow 18-24 hours to dry before recoating.
- Use a brush or roller to apply a second generous coat.

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- For best results use 2 coats of Prodec Stoep Paint.
- The spreading rate will vary with porosity and type of substrate. For uncoated new work 1 litre will cover about 6-8m². For subsequent coats and when applied to sealed or previously painted substrates, 1 litre will cover 8-10m².
- Clean application equipment with Prodec Mineral Turpentine.

COLOUR RANGE AND QUANTITIES

- Available in red oxide, grey, dark grey, chrome oxide green and black
- 1L, 5L and 20L

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- This material is highly flammable.
- Do not eat, drink or smoke while using this product.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za