



**MISCELLANEOUS PRODUCTS
TECHNICAL DATA SHEET**

MINERAL TURPENTINE

Use Prodec Mineral Turpentine for:	<ol style="list-style-type: none"> 1. Prodec Eggshell enamel paint 2. Prodec High gloss enamel paint 3. Prodec Procure 4. Prodec General Purpose Undercoat 5. Prodec Bonding Liquid 6. Prodec Pink Wood Primer 7. Prodec Solvent-based Plaster Primer 8. Prodec Stoep Paint 9. Prodec Floor Coat 10. Prodec Supergrade/Bituminous Aluminium 11. Prodec Non-Drip Enamel 12. Prodec Solvent-based Woodshield Coatings
Product Base	Aliphatic Hydrocarbon solvent with low toxicity.
Quantities	13. Available in 5L and 750ml containers.
Precautions	<ol style="list-style-type: none"> 14. This Product is a flammable liquid. With a Flash Point of Circa 37 Deg C 15. Never store in direct sunlight. 16. Store in a dry and cool place. 17. Familiarize yourself with your municipal and insurers regulations regarding storage of flammable liquids. 18. Avoid the inhalation of solvent vapours, which might lead to dizziness and even drowsiness. 19. Constant exposure to solvent vapours in high concentration can be detrimental to your health. 20. Never use This Product to wash or clean your hands or any part of the skin as it may cause skin irritation.