



PRIMERS & UNDERCOATS TECHNICAL DATA SHEET

DECORATORS SOLVENT-BASED PLASTER PRIMER



PRODUCT DESCRIPTION

Prodec Decorators Solvent-Based Plaster Primer is an alkali resistant, penetrating, binding and stabilising pigmented primer and sealer. It combines, in one product, the benefits of having good binding/substrate stabilizing plus good hiding power.

- For interior and exterior use
- For powdery, friable and very porous or stained substrates such as old paint, new friable or porous plaster and fillers.

Once Prodec Solvent-Based Plaster Primer has done its job these areas can be over-coated with a range of Prodec water and solvent based decorative products.

PRODUCT FEATURES

- Excellent penetrating and binding properties
- Excellent adhesion
- Excellent alkali-resistant properties
- Excellent stain-blocking properties
- Good hiding/obliterating power
- Estimated Dry Film Thickness: 35-45 Microns per coat when applied at 6-8m²/L
- Once a substrate is sealed with Prodec Solvent-Based Plaster Primer it can be over-coated with a wide range of Prodec water and solvent-based products

APPLICATION AREAS

- Powdery, friable, weathered or previously painted plaster areas
- Fire or nicotine stained areas
- New or previously painted Rhinolite surfaces

SURFACE PREPARATION

- **Previously painted surfaces:** remove all loose, flaking or bubbling paint, as well as all dust, foreign material or fungal and algal growth. Allow to dry.
- **Lime wash coated walls:** as far as possible remove lime wash with scraper blades, soft wire or hard fibre brushes, but be careful not to damage the plaster.
- **Dry (moisture content less than 15%) interior plaster surfaces:** sand carefully and remove dust.
- **Dry (moisture content less than 15%) exterior cement based fillers:** sand carefully and remove dust.

APPLICATION PROCEDURE

- Apply Prodec Decorators Solvent-Based Plaster Primer with a brush or roller.
- Allow 6 hours drying time before over coating.

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- Do not apply to exterior if rain is likely within 4-6 hours of application.
- Clean application equipment with Prodec Mineral Turpentine.
- Spreading rate will vary with substrate porosity but on average 1 litre will cover 6-8m².

COLOUR RANGE AND QUANTITIES

- Available in white. (Can be tinted to Pastel Shades on request)
- 1L, 5L and 20L

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za